



EN ISO 20345:2022 

DIVENTURE
BORMIO BOA®
70535-03L

S3S FO *CI SC LG SR

Size: 36-48
Weight: 670 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Oil industry, Farming and
Gardening



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
QRS02 Green

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX recycled insert - PS method

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY CCYCLED® SR
Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

Boa® lace length
L6 - 85cm



TECHNOLOGIES

Removable Insole
QRS02 GREEN

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements

KX GREEN RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

PU - PU
SOLE 70

SLIP RESISTANCE
EN ISO 20345:2022

	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP	SLIP RESISTANCE
BASIC CERAMIC WITH NALS	≥ 0.31	≥ 0.36	0,39
SR CERAMIC WITH GLYCERINE	≥ 0.19	≥ 0.22	0,20
			0,31

Other



FIT TO GO FURTHER™

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

