

EN ISO 20345:2022 

DIVENTURE  
**BRENNERO BOA®**  
 70534-03L

**S3S FO \*CI SC LG SR**

**Size:** 36-48  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Oil industry, Farming and  
 Gardening



## FEATURES

**UPPER**  
 Greased Nubuk Dakar Leather  
 Hydro 1,8-2,0 mm

**LINING**  
 3D Green Air 320 gr.

**ANTISLIP LINING**  
 DUALMICRO

**INSOLE**  
 QRS02 Green

**TOE CAP**  
 Fiber cap SXT





**RESISTANCE TO PERFORATION**  
 KX recycled insert - PS method

**TYPE**  
 Ankle boot

**SOLE**  
**PU DUAL-DENSITY CCYCLED® SR**  
 Two-component PU sole made from recycled Ccycled® material with additional LG and SC requirements and SR characteristics.

**Boa® lace length**  
 M4 - 115cm



PU - PU SOLE 70		SLIP RESISTANCE	
EN ISO 20345:2022			
<b>BASIC</b> CERAMIC WITH NAILS	FORWARD HEEL SLIP ≥ 0.31	<b>0,39</b>	
	BACKWARD FOREPART SLIP ≥ 0.36	<b>0,42</b>	
<b>SR</b> CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	<b>0,20</b>	
	BACKWARD FOREPART SLIP ≥ 0.22	<b>0,31</b>	

## TECHNOLOGIES

**Removable Insole**  
**QRS02 GREEN**

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



**Protection elements**

**KX GREEN** RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Torsional stability**  
**STABIL • ACTIVE**

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**

**ESD**

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**  
**BOA FIT TO GO FURTHER.™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

