

EN ISO 20345:2022



DIVENTURE

**BRENNERO BOA®**  
70534-03L

**S3S FO \*CI SC LG SR**

**Size:** 36-48  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**

Building, Wood-metal carpentry,  
Oil industry, Farming and  
Gardening



## FEATURES

### UPPER

Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

QRS02 Green

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX recycled insert - PS method

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

#### Boa® lace length

M4 - 115cm

## TECHNOLOGIES

### Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



### Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Torsional stability




Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.





### PU - PU

SOLE 70

### SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,39	
	BACKWARD FOREPART SLIP ≥ 0.36	0,42	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,20	
	BACKWARD FOREPART SLIP ≥ 0.22	0,31	

### Other



**FIT TO GO  
FURTHER.™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

