



EN ISO 20345:2022



DIVENTURE
MARMOLADA
70539-01L

S3S FO *CI SC LG SR

Size: 36-48
Weight: 740 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Oil industry, Farming and
Gardening



FEATURES

UPPER

Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX recycled insert - PS method

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



RESISTANT
TO 3.0 mm.
NAILS

fibercap sxt

Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Torsional stability




Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.



PU - PU

SOLE 70

SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,39	
BACKWARD FOREPART SLIP ≥ 0.36	0,42	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20	
BACKWARD FOREPART SLIP ≥ 0.22	0,31	