



EN ISO 20345:2022



DIVENTURE  
**MARMOLADA**  
70539-05L

**S7S FO \*CI SC LG SR**

**Size:** 36-48  
**Weight:** 750 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Oil industry, Farming and  
Gardening



## FEATURES

### UPPER

Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Reflex insert

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

QRS02 Green

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX recycled insert - PS method

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

## TECHNOLOGIES

### Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



### Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other



The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.



### PU - PU

SOLE 70

### SLIP RESISTANCE

EN ISO 20345:2022

**BASIC**  
CERAMIC WITH  
NAILS

FORWARD  
HEEL SLIP  
≥ 0.31

0,39

BACKWARD  
FOREPART SLIP  
≥ 0.36

0,42

**SR**  
CERAMIC WITH  
GLYCERINE

FORWARD  
HEEL SLIP  
≥ 0.19

0,20

BACKWARD  
FOREPART SLIP  
≥ 0.22

0,31