



EN ISO 20345:2022



RESOLUTE FORZA HIGH BOA®

45477-09L

S7S FO HI *CI SC HRO SR

Size: 36-48
Weight: 670 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas


FEATURES

UPPER

 Full Grain leather Hydro 1,8-2,0 mm
 Mesh H.T. no ladder

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX recycled insert - PS method

TYPE

Ankle boot

SOLE

**PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR**

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM RECYCLED (≥30%) rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with SR Antislip standard.

Boa® lace length
 L+1 - 115cm

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic H C control
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

HDry
 +WATERPROOF UPPER

The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.





PU - RUBBER

SOLE 45


SLIP RESISTANCE

EN ISO 20344:2021

BASIC
 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,45	
BACKWARD FOREPART SLIP ≥ 0.36	0,47	

SR
 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,28	
BACKWARD FOREPART SLIP ≥ 0.22	0,25	