



MADE IN ITALY

Model	Line	Standard
MONTAUK	ENDURANCE	EN ISO 20345:2011
Article	Protection	Availability in stock
81154-00L	S3 SRC	



Preview	Sole	PU Dual-Density SRC passed
---------	------	----------------------------



Two-component PU sole with anti-wear scaffold cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Ankle boot	
Upper	Full Grain leather Hydrotech Micra Coagulated PU	
Lining	3D Air circulation 320 gr.	
Antislip Lining	DUALMICRO	
Removable Insole	Flyfit	
Sole	PU Dual-Density SRC passed	
Toe Cap	C.T.C. - Composite Toe Cap	
Anti-Perforation	ZERO (k) ANTIPERFORATION	
Size	38-48	Weight gr. 670

Working Environment

Building, Wood-metal carpentry, Farming and Gardening, Polivalente.

SRC

SRC (SRA+SRB)		
	FLAT	Sole 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$ HEEL $\geq 0.28$	0.52
SRB STEEL + GLYCEROL	FLAT $\geq 0.18$ HEEL $\geq 0.13$	0.23

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic



Wire Electricity Discharge  
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Symbols



Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it