



EN ISO 20344:2011



CRYSTAL
BIELLA
86205-00

S2 *CI SRC

Size: 35-39 40-48
Weight: 490 gr.

Fit: 11

Working Environment:
Food and Chemical industry,
Ho.Re.Ca.



FEATURES

UPPER

MicroFiber XPRO 1,8-2,0 mm

LINING

Bacteriostatic Teklife 3D

ANTISLIP LINING

DUALMICRO

INSOLE

Flyfit

TOE CAP

Fiber cap SXT

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

TECHNOLOGIES

Removable Insole




The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.



Protection elements



Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



SRC (SRA+SRB)



SOLE 86
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.40
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.