



EN ISO 20345:2022



RESOLUTE  
**ANVERSA BOA**  
45553-00L

**S7S FO HI \*CI SC HRO SR**

**Size:** 36-48  
**Weight:** 760 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Special



**FEATURES**

**UPPER**

Full Grain leather Hydro 1,8-2,0 mm  
Reflex insert

**LINING**

3D Green Air 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

QRS02 Green

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

KX Antiperforation recycled PS

**TYPE**

Ankle boot

**SOLE**

**PU-RUBBER VIBRAM ECOSTEP PRO-HRO-SR**

Sole with anti-wear scaff cap. Outsole in VIBRAM RECYCLED ( $\geq 30\%$ ) rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with SR Antislip standard.

**Boa® lace length**  
L+1 - 115cm

**TECHNOLOGIES**


**Removable Insole**



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



**Protection elements**



Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**

**metatarsal protection**

D30 anatomical protection, resistant up to 100 Joules, to protect the metatarsal against falling metal sheets or similar







**PU - RUBBER**

SOLE 45

**SLIP RESISTANCE**

EN ISO 20344:2021

|                                     |                                    |             |   |
|-------------------------------------|------------------------------------|-------------|---|
| <b>BASIC</b><br>CERAMIC WITH NAILS  | FORWARD HEEL SLIP $\geq 0.31$      | <b>0,45</b> |  |
|                                     | BACKWARD FOREPART SLIP $\geq 0.36$ | <b>0,47</b> |  |
| <b>SR</b><br>CERAMIC WITH GLYCERINE | FORWARD HEEL SLIP $\geq 0.19$      | <b>0,28</b> |  |
|                                     | BACKWARD FOREPART SLIP $\geq 0.22$ | <b>0,25</b> |  |

**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**



The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

