



EN ISO 20345:2011



RESOLUTE
SCATTO HIGH
BOA®

43459-01L

S3 CI SRC

Size: 36-48
Weight: 660 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



FEATURES

UPPER

MicroFiber Suede 1,8-2,0 mm
MicroFiber Suede with Scratch
Bumper 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Qrs01

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

Boa® lace length

L6 - 110cm

TECHNOLOGIES


Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



PU - PU

SOLE 43

SLIP RESISTANCE

EN ISO 20344:2021

BASIC
CERAMIC WITH
NAILS

FORWARD
HEEL SLIP
≥ 0.31

0,40

BACKWARD
FOREPART SLIP
≥ 0.36

0,39



SR
CERAMIC WITH
GLYCERINE

FORWARD
HEEL SLIP
≥ 0.19

0,33

BACKWARD
FOREPART SLIP
≥ 0.22

0,32



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



PROGRESSIVE CUSHIONING AND ADAPTIVE STABILITY

D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.

