



EN ISO 20347:2022

SCOUT

TONALE

33329-09

06 FO HI *CI HRO SC SR

Size: 36-48 Weight: 700 gr.

Fit: 11

Working Environment:

Farming and Gardening,

Mountains







FEATURES

UPPER

Greased Nubuk Dakar Leather Hydro 1,8-2,0 mm Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE Qrs01

TOE CAP

TYPE

Ankle boot

PU - RUBBER

CERAMIC WITH GLYCERINE

SOLE

PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and comfortable. Modular overtoe to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled opencell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toecap, with no anti-perforation



Lateral stability

dynamic H control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



SOLE 30 EN ISO 20344:2021 **BASIC** ≥ 0.31 CERAMIC WITH NALS BACKWARD FOREPART SL ≥ 0.36 FORWARD HEEL SLIP ≥ 0.19

BACKWARE

A E FO WPA HI *CI WR SC HRO SR

SLIP RESISTANCE

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user



