



EN ISO 20345:2022



SKIPPER

**VELA**

**94557-01L**

**S3S FO SR**

**Size:** 38-48

**Weight:** 560 gr.

**Fit:** 11

**Working Environment:**

Logistics and Light Industry, Components and Automotive, ESD Areas



## FEATURES

### UPPER

Drummed Suede Leather Hydro  
1,6-1,8 mm  
Digitex Hydro Airy

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### SOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

### TYPE

Low Shoe

### SOLE

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements



RESISTANT TO 3.0 mm. NAILS



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



### PU - PU

SOLE 94

### SLIP RESISTANCE

EN ISO 20344:2021

**BASIC**  
CERAMIC WITH NAILS

FORWARD HEEL SLIP  $\geq 0.31$

**0,34**

BACKWARD FOREPART SLIP  $\geq 0.36$

**0,40**

**SR**  
CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP  $\geq 0.19$

**0,29**

BACKWARD FOREPART SLIP  $\geq 0.22$

**0,40**